Datasheet





CAT. NO. 659013LI, 659014LI



659013LI

Cat. No.	659013LI	659014LI			
Finish	White	Black			
Operating Mode	Non- Maintained				
Nominal Input Voltage	230 - 240 V a.c. 50 Hz				
Battery	Li-ion 6.4 V, 1.5 Ah				
Power Consumption	1.5 W (Charge) / 0.7 W (Standby)				
Inrush Current	5 A peak				
Light Source Life (LSL)	100,000 hrs				
Body Constructions	Polycarbonate (Satellite head), Steel (Enclosure)				
Operating Temperature	10° C to 40° C				
IP Rating	IP20				
Compliance	AS/NZS 2293, AS/NZS 60598, AS/NZS 4268, AS CISPR 15				
Product Marking					









LED Satellite Surface Mount - D50

CAT. NO. 659013LI, 659014LI





FEATURES

- Embedded Bluetooth for smart device connectivity.
- Low Power Wide Area Network type of communications utilising the LoRa platform.
- LoRa communication to maximise reliability, coverage and infiltration.
- iSmart[™] temperature sensing technology for the Li-ion battery.
- Electronics designed to lengthen the life of the battery, minimising maintenance costs.
- Environment friendly battery.
- Easy to install.
- One high Brightness LED.
- 5 Year Warranty.
- Designed and Manufactured in Australia.

SPACING TABLE

Maximum spacings between luminaires for 0.2 lux (Australia)

Mounting Height (m)	2.4	2.7	3.0	3.3	3.6	4.0
Α	13.2	14.8	16.5	18.1	19.8	21.8
В	13.2	14.8	16.5	18.1	19.8	21.8


As per AS/NZS 2293:2018


Maximum spacings between luminaires for 1.0 lux (New Zealand)

Mounting Height (m)	2.4	2.7	3.0	3.3	3.6	4.0
Α	10.5	10.8	11.0	11.2	11.4	11.5
В	10.5	10.8	11.0	11.2	11.4	11.5

As per AS/NZS 2293:2018

DIMENSIONS





Legrand - Australia 1300 369 777 www.legrand.com.au ABN 31 000 102 661

Legrand - New Zealand 0800 476 009 www.legrand.co.nz Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

