

Datasheet

Aqua

Weatherproof Single Powerpoint 10A IP53, with USB Type A&C

CAT. NO. **RWL787USBMG**



A brand of **legrand**



RWL787USBMG

Cat. No.	RWL787USBMG
Description	Aqua Weatherproof Single Powerpoint 10 A IP53, with USB Type A&C
Colour	Misty Grey (MG)
Mounting	Surface mount
IP Rating	IP53 when flap closed and IP20 when flap opened
Current Rating	10 A
Nominal Input Voltage	230 - 240 V a.c. 50 Hz
Nominal Output Voltage (USB)	5 V d.c.
Nominal Output Current (USB)	5 A total (2.4 A on Type A, 3 A on Type C)
Stand-by Power Consumption	<0.1 W
Energy Efficiency	Level VI ≥ 84% measured at USB socket output side
Protection Class	Class II
Overload Protection (USB charger)	5.5 A ± 0.2 A
Surge Protection (USB charger)	150 Joules
Operating Temperature	5°C to 40°C
Product Dimensions (W x H x D)	122 x 85 x 85 mm
Material	UV-stabilised polycarbonate
Compliance	AS/NZS 60950.1, AS/NZS4665, AS/NZS 3112

Aqua

Weatherproof Single Powerpoint 10A IP53, with USB Type A&C

CAT. NO. **RWL787USBMG**



A brand of **legrand**



FEATURES


- Durable
- 10 A
- IP53 with USB flap closed
- Type A+C USB charger
- USB superfast charging: 5 A capacity

BOX PACKAGING


Single Product		
Cat. No.	Barcode	Dimensions (W x H x D)
RWL787USBMG	9321001484004	126 x 90 x 90 mm

Outer Box (QTY 5)		
Cat. No.	Barcode	Dimensions (W x H x D)
RWL787USBMG	9321001484967	445 x 130 x 140 mm

IP53



IP20



Legrand - Australia
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

Legrand - New Zealand
0800 476 009
www.hpm.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.

