

Datasheet

Professional Flush Mounted Smoke Alarm

CAT NO. 643087



Cat No	643087
Supply voltage	230-240V a.c.
Frequency	50Hz
Backup Battery	3V Lithium battery (non replaceable)
Temperature Range	+0°C to ~ +40°C
Humidity Range	10-97% at 20°C
Siren sound level	>85 dB at 3 metres
Unit Size	Ø110 x 77mm
Ceiling Cut-out Size	Ø90mm
Protrusion from ceiling	Ø25mm
Depth into ceiling	52mm
Maximum Lifespan	10 years

Professional Flush Mounted Smoke Alarm

CAT NO. **643087**



Single product	
Cat No	Barcode
643087	9321001474708

Outer box (QTY 6)	
Cat No	Barcode
643087	9321001474715

Photoelectric

Photoelectric smoke alarms 'see' the smoke. They detect visible particles of combustion. They respond to a wide range of fires, but they are particularly responsive to smouldering fires and the dense smoke given off by foam filled furnishings or overheated PVC wiring.

Advantages

- Ideal for smouldering fire and dense smoke
- Not as prone to cooking nuisance alarms as ionisation alarms
- Contain no radioactive material
- Suitable for general use
- Interconnectable – up to 20 units
- Flush mounted
- Power and alarm indicator
- Easy access for wiring
- Hush/Test button
- 10 Year Lithium Battery
- Low battery indication (audio and visual)
- Duct cover to protect the device during installation
- Smoke detector interface (643086) available separately to interconnect with other appliances, circuits and systems e.g. lighting and exhaust fans
- Quick installation into ceiling due to ceiling clamps
- Compact depth into ceiling (52mm), adapted to all types of roofing

Legrand - AUS
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand - NZ
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Specifications may change without notice.