

Datasheet



Aqua Life

Weatherproof Single Powerpoint 10A IP53, with USB Type A&C

CAT NO. **WL787USBLG**, **WL787USBCG**



WL787USBLG



WL787USBCG

Cat No	WL787USBLG	WL787USBCG
Description	Aqua Life Weatherproof Single Powerpoint 10A IP53, with USB Type A&C	
Colour	Limestone Grey (LG), Cement Grey (CG)	
Mounting	Surface mount	
IP rating	IP53 when flap closed, IP20 when flap opened	
Current rating	10A	
Nominal input voltage	240V a.c.	
Nominal output voltage (USB)	5V d.c.	
Nominal output current (USB)	5A total (2.4A on Type A, 3A on Type C)	
Stand-by power consumption	<0.1W	
Energy efficiency	Level VI \geq 84% measured at USB socket output side	
Protection class	Class II	
Overload protection (USB charger)	5.5A \pm 0.2A	
Surge protection (USB charger)	150 Joules	
Operating temperature	5° to 40°C	
Product dimensions (W x H x D) mm	122 x 85 x 85	
Material	UV-stabilised polycarbonate	
Compliance	AS/NZS 60950.1, AS/NZS4665, AS/NZS 3112	

Aqua Life

Weatherproof Single Powerpoint 10A IP53, with USB Type A&C

CAT NO. **WL787USBLG, WL787USBCG**



WL787USBLG




WL787USBCG

Single product		
Cat No.	Barcode	Dimensions (W x H x D)
WL787USBLG	9321001484172	126 x 90 x 90mm
WL787USBCG	9321001484356	126 x 90 x 90mm


Outer box (QTY 5)		
Cat No.	Barcode	Dimensions (W x H x D)
WL787USBLG	9321001485131	445 x 130 x 105mm
WL787USBCG	9321001485315	445 x 130 x 105mm

- Durable
- 10A
- IP53 with USB flap closed
- Type A+C USB charger
- USB superfast charging: 5A capacity

IP53



IP20



Legrand Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.