


Economy Weatherproof LED Batten
- SPU version with ON/OFF sensor

CAT. NO. **659527LI, 659529LI, 659531LI**



Cat. No.		659527LI	659529LI	659531LI
Description		L6 LED BATTEN MW ON/OFF	L12 LED BATTEN MW ON/OFF	L15 LED BATTEN MW ON/OFF
Supply voltage		230 - 240 V a.c. 50Hz		
Operation Mode		Switched Maintained		
Classification C ₀ /C ₉₀		C ₀ : D63, C ₉₀ : C125	C ₀ : D125, C ₉₀ : D80	C ₀ : D125, C ₉₀ : D80
Battery		Li-ion 12.8 V, 1.5 Ah	Li-ion 12.8 V, 3.3 Ah	
Light source		LED (4000 K)		
Chromaticity Tolerance		MacAdam Ellipse: 4 SDCM		
Luminous flux (lm)	Mains mode	2,100	4,600	5,700
	Emergency mode	470	900	
Power (W)	Mains only	23	49	56
	Emergency pack	3	7	10
	Total	26	56	66
Sensor type		Microwave		
Luminaire efficacy (lm/W)		81	82	86
Power factor		0.90	0.96	0.97
Inrush current		TBA	TBA	TBA
Driver type		Fixed output / Non-Dimmable		
IK rating		IK08		
IP rating		IP65		
Retaining clips		304 Stainless Steel		
Body construction		Polycarbonate		
Diffuser		Opal polycarbonate		
Length (mm)		664	1274	1574
Weight (kg)		1.8	2.9	3.4
Compliance		AS/NZS 2293, AS/NZS 60598		
Product Marking				

