Datasheet

Easy kit Connected - 2 wire

CAT. NO. **318013**



EASY KIT CONNECTED




Cat. No.	318013
Description	Door Entry Kit: Entrance panel, Internal screen and plug-in power supply
Nominal Supply Voltage	230 - 240 V a.c. 50 Hz
Mounting	Surface Mount
Connection Entrance Panel/Internal Screen	2 wire
Detection Angle (Entrance panel)	95°
IP Rating (Entrance panel)	IP54
IK Rating (Entrance panel)	IK07
Operating Temperature	-15°C to +50°C
Screen (Internal screen)	7'' LCD
Door lock compatibility	12/24 V a.c. 1A 12/24 V d.c. 1A


Easy kit Connected - 2 wire

CAT NO 318013

ticino

DIMENSIONS







FEATURES

7"handsfree connected video monitor

- 2 wire connection to external panel.
- Easy to install provided with plug-in power supply.
- Ability to add extra monitors Cat. No. 332853 (to be purchased separately)
- Surface mounted
- Connected Kit: Monitor and interacts with people ringing at the door, wherever you are.
- Compatible with Netatmo cameras: The Easy kit App enables you to view your door entry and Netatmo cameras on the same App.

Video entrance panel with LED lights

- Robust Zamak construction
- Weather protection: IP54
- Impact protection: IK07
- Wide angle camera up to 95°
- Surface mounted
- Rain shield included
- Maximum of 2 entrance panels per installation. Additional Entrance Panel. Cat. No. 331860 (to be purchased separately)

PACKAGING

Single Produ	ict (Qty 1)	
Barcode	8005543674840	

Outer Box (0	uter Box (Qty 6)	
Barcode	8005543674857	

