Datasheet

PHOTOELECTRIC SMOKE ALARM

CAT. NO. **643085**











9V D.C. BATTERY BACKUP







PRODUCT SPECIFICATIONS

Cat. No.	643085		
Colour	White		
Supply Voltage	230-240 V ~ 50 Hz		
Power Source	Mains powered		
Sensor Type	Photoelectric		
Mounting Type	Surface (ceiling or wall) - screws		
Interconnect Type	Wired (up to 20 interconnected smoke alarms)		
Battery Type	Replaceable 1 year 9V d.c. battery (backup)		
Product Size	Ø 147 x 49 mm		
Temperature Range	0° C to +40 ° C		
Humidity Range	10-95 % at 20° C (non-condensing)		
Alarm Volume	> 85 dBA at 3 metres*		
Recommended Lifespan	10 Years		
Alarm Pattern	ISO 8201		
Quality System	ISO 9001		

^{*} Tested under laboratory conditions.

Datasheet

PHOTOELECTRIC SMOKE ALARM

CAT. NO. **643085**



FEATURES AND BENEFITS

- Detects visible particles of combustion
- Responsive to smouldering fires and dense smoke which occur in the majority of domestic fires
- Best protection for alerting occupants as when one smoke alarm sounds, all interconnected smoke alarms will sound simultaneously
- Clip on the mounting base which has multiple fixing points for easy installation and maintenance
- LED indicators for AC power, battery status and alarm
- Wide smoke entry vents for early smoke detection
- Large single test and hush button easy to use and silence unwanted alarms
- Photoelectric smoke alarm for fast response to smouldering fires
- Sealed mesh protector over sensor chamber to prevent insect and dust contamination
- UV resistant to prevent discolouring
- Electronics coated to prevent build up of heat and condensation caused by humidity and high temperatures

SHIPPING

Single Product			
Cat. No.	Barcode	Product Weight (gms)	Single Box Dimension (mm)
643085	9321001433958	268	155 x 155 x 70

Outer Box (24)					
Cat. No.	Barcode	Outer Box Weight (kg)	Outer Box Dimension (mm)		
643085	9321001433972	6.4	637 x 237 x 223		

Legrand Australia 1300 369 777 www.legrand.com.au ABN 31 000 102 661

Paper du l'org. du