

Data Sheet

Professional Photoelectric Smoke Alarm, 240V

CAT NO. 643085



Cat No	643085
Colour	White
Type	Photoelectric
Diameter	147mm
Depth	49mm
Mounting centre	84mm
Siren sound level	85db at 3m
Supply voltage	230-240V a.c.

Data Sheet

Professional Photoelectric Smoke Alarm, 240V



CAT NO. **643085**



Product specifications		
Cat No	643085	Quantity
Single Barcode	9321001433958	1
Inner Barcode	9321001433965	6
Outer Barcode	9321001433972	24

Photoelectric

Photoelectric smoke alarms 'see' the smoke. They detect visible particles of combustion, eg smouldering cigarette smoke. They respond to a wide range of fires, but they are particularly responsive to smouldering fires and the dense smoke given off by foam filled furnishings or overheated PVC wiring.

Advantages

- Good for smouldering fire and dense smoke
- Not as prone to cooking nuisance alarms as ionisation alarms
- Contain no radioactive material
- Suitable for general use
- Interconnectable – up to 20 units
- Surface mounting for easy fit-off
- Power and alarm indicator
- Easy access for wiring
- Hush/Test button
- 9V battery back-up included
- Low battery indication (audio and visual)
- Duct cover to protect the device during installation
- Smoke detector interface (643086) available separately to interconnect with other appliances, circuits and systems e.g. lighting and exhaust fans

HPM Legrand - AUS
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.legrand.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

* Specifications may change without notice