Data Sheet

LUNA Dimmable LED Panel Light Kit 18W, IP44 CAT NO. LPA013KWE






LUNA LED Panel Light

Cat no.	Description	Wattage	Ceiling Cut-out	Ceiling Depth	Fascia Diameter	Lumens	Colour Temp	Beam Angle	CRI	IP Rating
LPA013KWE	White LED Panel Light 18W LED, Warm White with Dimmable Driver	18W	225mm	30mm	250mm	1440lm	3000K	103°	80+	IP44

LUNA Dimmable LED Panel Light Kit 18W, IP44 CAT NO. LPA013KWE





■ 1440 lumens

- 18 Watts
- High efficacy: 80lm/w
- IP44
- Trailing and leading edge dimmer compatible
- Smooth dimming range
- Quick-connect wiring between fitting and driver (1m lead)
- Supplied with flex and plug
- Wide beam angle 103°
- IC insulation rating: A type IC recessed luminaire can be installed with building material that can be exposed continuously to temperatures up to 90°C. Such insulation can cover and abut the side of the luminaire
- Slimline alternative to oyster lights
- Low profile, only 30mm depth
- Up to 20 years life span
- 6-year warranty
- Driver suitable for standard slab and canister

Single product					
Cat No	Single Barcode	Dimensions	Weight		
LPA013KWE	9321001432999	260 x 260 x 50mm	795g		

Outer box (Qty 10)					
Cat No	Barcode	Dimensions	Weight		
LPA013KWE	9321001433187	640 x 290 x 290mm	9.3kg		

Compatible dimmers	Max. lamps per dimmer	Dimming range	
Legrand Excel Life EM400A3P	8	100%-5%	
Legrand Excel Life EM250T	5	100%-10%	
Legrand Excel Life EM400T	8	100%-10%	
Legrand Arteor AR400T	8	100%-10%	
Legrand Arteor AR400A3P	8	100%-5%	
HPM 250T/250L	5	100%-10%	
HPM 400T/400L	8	100%-10%	
HPM 700T/700L	14	100%-25%	
HPM 1000T/1000L	20	100%-25%	

HPM Legrand - AUS 1300 369 777 www.hpm.com.au ABN 31 000 102 661

HPM Legrand - NZ 0800 476 009 www.hpm.co.nz

A Group brand

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.