

QUICK-FIT CEILING FANS



CLASSIC STREAMLINE DESIGN

We believe fans should be designed to be timeless and discreet.



WHETHER YOU'RE IN THE TROPICS, THE OUTBACK, THE SUBURBS, OR REMOTE NEW ZEALAND, WE WANT TO KEEP YOU COOL AND COMFORTABLE WITHOUT COSTING YOU A FORTUNE.

So we've designed and engineered our fans in Australia to provide maximum performance for minimum energy consumption. We've also focused on making them easier to install.

Simple, reliable and good value for money; you can't beat that.



QUICK-FIT WIRING

for super fast installation. No need to bring up the fan on the ladder



REMOTE CONTROL compatible with all models. Perfect for retrofit installations



QUICK-FIT BLADES for less hassle and rapid fit-off



MAXIMUM AIRFLOW enables maximum cooling whilst maintaining quiet operation



PRE-WIRED REPLACEABLE DOWNRODS for easy extension




LIGHT ADAPTABLE for convenience and space-saving



HANG-SURE & J-HOOK MODELS for level and inclined ceilings




AUSTRALIAN DESIGNED & ENGINEERED for quality guaranteed





HANG-SURE MOUNTING

Suitable for all ceiling types including inclined ceilings up to a 20° angle



J-HOOK MOUNTING

Suitable for level ceiling only

OPTIONAL ACCESSORIES

REMOTE CONTROL KIT* (CFREMOTEJ/CFREMOTEH)

- 2, 4 & 6 hour timer
- Low, Med & High fan speed
- Low, Med & High light
- Compatible with all models
- Wall bracket included

OYSTER LIGHT KIT (CFOLWE / CFOLBS)

- Available in White (WE) and Brushed Stainless Steel (BS)
- Compatible with the entire range
- Easy fit-off

(Note: globe not included)

CLIPPER LIGHT KIT (CFCLWE/CFCLBS)

- Available in White (WE) and Brushed Stainless Steel (BS)
- Compatible with the entire range
- Easy fit-off
- (Note: globe not included)









GUIDE TO CHOOSING THE RIGHT FAN

Room dimension	Up to 12m ²	12 – 27m²	27+m²
Suggested fan size	900mm	1200mm	1400mm

· []

SUMMER & WINTER MODES EXPLAINED

WE'VE ADDED A SIMPLE TOGGLE SWITCH ON ALL OUR FANS SO IT'S EASY TO SWITCH BETWEEN SUMMER MODE FOR THE WARMER MONTHS AND WINTER MODE FOR THE COOLER MONTHS. THIS OPTIMISES THE FAN'S PERFORMANCE AND INCREASES COMFORT.

Summer and Winter mode switch

Ò

SUMMER MODE: In the warmer months, you want the blades to rotate clockwise to push cool air down. This creates a wind chill effect and evaporates perspiration from skin to keep everyone comfortable.

*

WINTER MODE: In the cooler months, you want the blades to rotate counter-clockwise at a low speed to pull air up. A gentle updraft will push warm air, which naturally rises to the ceiling, down along the walls to the floor to keep everyone snug.

By optimising air flow, ceiling fans can significantly reduce airconditioning and heating bills.

ENERGY-SAVING TIP

316 Marine Grade Stainless Steel SERIES

• ALL EXPOSED COMPONENTS MADE OF 316 MARINE GRADE STAINLESS STEEL

This ensures total resistance to harsh environments (eg. humidity, salinity) Perfect for homes in coastal areas and alfresco dining areas.



仐

FEATURES

- FULL 316 marine grade stainless steel construction (body, blades, screws, brackets etc.) for the best corrosion resistance
- 3 blades
- Motor: 65W
- Mounting Options: Hang-sure - inclined and level ceilings J-Hook - level ceiling only
- Quick-fit wiring for super fast installation
- Quick-fit blades
- Light adaptable oyster and clipper light kits available
- Light adaptable
- Reversible operation for Summer and Winter
- Heavy-duty sealed bearings
- Includes 3-speed Excel Life white fan controller
- Compatible with remote control CFREMOTEJ (J-Hook) & CFREMOTEH (Hang-sure)
- 3 year warranty

PERFORMANCE

Ca	t No	Fan Speed	RPM [Rotations per Minute]	Power [Watts]	Airflow [m³/H]
F	CF12J316L	Low	150	13	2,940
1200mm	&	Medium	260	33	6,720
12	CF12H316L (Hang-sure)	High	320	60	10,020
E	CF14J316L	Low	115	13.2	3,480
1400mm	&	Medium	210	33.5	7,800
14	CF14H316L (Hang-sure)	High	280	60	11,040

RECOMMENDED ACCESSORIES

Grid & Plate

ED770/2GPLWE

Remote Control Kit








Dimmer

EM400A3PWE

ELONE

CFREMOTEH (Hang-sure) CFREMOTEJ (J-Hook)



304 Stainless Steel

••••• GUIDE TO STAINLESS

STEEL GRADE 316 SERIES: Best 304 SERIES: Great 430 SERIES: Good

FEATURES

- Quick-fit 304 stainless steel blades for great corrosion resistance
- 3 blades
- Motor: 65W
- Mounting Options: Hang-sure - inclined and level ceilings J-Hook - level ceiling only
- Quick-fit wiring for super fast installation
- Light adaptable oyster and clipper light kits available
- Reversible operation for Summer and Winter
- Heavy-duty sealed bearings
- Includes 3-speed Excel Life white fan controller
- Compatible with remote control CFREMOTEJ (J-Hook) & CFREMOTEH (Hang-sure)
- 3 year warranty

Dimmer

EM400A3PWE

PERFORMANCE

Ca	t No	Fan Speed	RPM [Rotations per Minute]	Power [Watts]	Airflow [m³/H]
F	CF12J304	Low	150	13	2,940
1200mm	(J-HOOK) &	Medium	260	33	6,720
12	CF12H304 (Hang-sure)	High	320	60	10,020
E	CF14J304	Low	115	13.2	3,480
1400mm	&	Medium	210	33.5	7,800
14	CF14H304 (Hang-sure)	High	280	60	11,040

RECOMMENDED ACCESSORIES





430 Stainless Steel





FEATURES

- Quick-fit 430 stainless steel blades for good corrosion resistance
- 3 blades
- Motor:
 55W (900mm)
 65W (1200 &1400mm)
- Mounting Options: Hang-sure - inclined & level ceilings J-Hook - level ceiling only
- Quick-fit wiring for super fast installation
- Light adaptable oyster and clipper light kits available
- Reversible operation for Summer and Winter
- Heavy-duty sealed bearings
- Includes 3-speed Excel Life white fan controller
- Compatible with remote control CFREMOTEJ (J-Hook) & CFREMOTEH (Hang-sure)
- 3 year warranty

PERFORMANCE

Cat	t No	Fan Speed	RPM [Rotations per Minute]	Power [Watts]	Airflow [m³/H]
Ľ	CF9JBS	Low	160	7	1,500
900mm	&	Medium	260	13.5	2,800
6(CF9HBS (Hang-sure)	High	360	46	4,920
E	CF12JBS	Low	150	13	2,940
1200mm	(J-HOOK) &	Medium	260	33	6,720
12	CF12HBS (Hang-sure)	High	320	60	10,020
E	CF14JBS	Low	115	13.2	3,480
1400mm	&	Medium	210	33.5	7,800
14	CF14HBS (Hang-sure)	High	280	60	11,040



Clipper

CFCLBS (Brushed Stainless Steel)

Remote Control Kit



CFREMOTEH (Hang-sure) CFREMOTEJ (J-Hook)



Oyster

RECOMMENDED ACCESSORIES

CFOLBS (Brushed Stainless Steel)

Grid & Plate



ED770/2GPLWE

Recommended when using light kits - insert the fan controller (included in box with fan) and dimmer mechanism in one plate.

Dimmer

EM400A3PWE

Aluminium

• WHY 3 OR 4 BLADE?

This is a question of aesthetic preference. Both 3 and 4 blade fans perform equally well.





FEATURES

- Quick-fit white aluminium blades
- 3 and 4 blade options Motor:
- 55W (900mm) 65W (1200 &1400mm)
- Mounting Options: Hang-sure - inclined & level ceilings J-Hook - level ceiling only
- Quick-fit wiring for super fast installation
- Light adaptable oyster and clipper light kits available
- Reversible operation for Summer and Winter
- Heavy-duty sealed bearings
- Includes 3-speed Excel Life white fan controller
- Compatible with remote control CFREMOTEJ (J-Hook) & CFREMOTEH (Hang-sure)
- 3 year warranty

PERFORMANCE

Ca	t No	Fan Speed	RPM [Rotations per Minute]	Power [Watts]	Airflow [m³/H]
3 E	BLADE FANS		,		
Ę	CF9JWE	Low	160	7	1,500
900mm	&	Medium	260	13.5	2,800
6	CF9HWE (Hang-sure)	High	360	46	4,920
F	CF12JWE	Low	150	13	2,940
1200mm	&	Medium	260	33	6,720
12	CF12HWE (Hang-sure)	High	320	60	10,020
E	CF14JWE	Low	115	13.2	3,480
400mm		Medium	210	33.5	7,800
0114114	CF14HWE (Hang-sure)	High	280	60	11,040
4 E	BLADE FANS				
E	CF12J4WE	Low	125	13	3,000
1200mm	&	Medium	220	33	6,360
12	CF12H4WE (Hang-sure)	High	290	61.5	10,800
E	CF14J4WE	Low	105	13	3,360
1400mm	&	Medium	185	33	7,800
14	CF14H4WE (Hang-sure)	High	255	62	11,880

RECOMMENDED ACCESSORIES



CFREMOTEH (Hang-sure) CFREMOTEJ (J-Hook)



CFOLWE

Grid & Plate

ED770/2GPLWE

Recommended when using light kits - insert the fan controller (included in box with fan) and dimmer mechanism in one plate.

Dimmer

EM400A3PWE

Rattan

• RATTAN A perfect complement to traditional and country style homes.

RECOMMENDED ACCESSORIES



(J-Hook)



CFOLWE (White)

Grid & Plate



ED770/2GPLWE

EM400A3PWE

Dimmer

Recommended when using light kits - insert the fan controller (included in box with fan) and dimmer mechanism in one plate.

FEATURES

- Quick-fit white timber and rattan blades
- 4 blades
- Motor:
- 65W (1300mm) Mounting Options:
- Hang-sure inclined & level ceilings
- Quick-fit wiring for super fast installation
- Light adaptable oyster and clipper light kits available
- Reversible operation for Summer and Winter
- Heavy-duty sealed bearings
- Includes 3-speed Excel Life white fan controller
- Compatible with remote control CFREMOTEJ (J-Hook) & CFREMOTEH (Hang-sure)
- 3 year warranty

PERFORMANCE

Cat No	Fan Speed	RPM [Rotations per Minute]	Power [Watts]	Airflow [m³/H]
CF13HAW	Low	85	13	1,530
	Medium	150	33	4,800
	High	200	61.5	7,800

Range

Cat No	Diameter (mm)	Mounting	Finish	Blades	Maximum Airflow (m³/H)	RPM High / Medium / Low
316 MARI	NE GRADE	STAINLESS ST	TEEL SERIES			
CF12H316L	1200	Hang-sure	FULL MARINE GRADE 316 STAINLESS STEEL	3	10,020	H320, M260, L150
CF12J316L	1200	J-Hook	FULL MARINE GRADE 316 STAINLESS STEEL	3	10,020	H320, M260, L150
CF14H316L	1400	Hang-sure	FULL MARINE GRADE 316 STAINLESS STEEL	3	11,040	H280, M210, L115
CF14J316L	1400	J-Hook	FULL MARINE GRADE 316 STAINLESS STEEL	3	11,040	H280, M210, L115
304 STAIN	NLESS STE	EL SERIES				
CF12H304	1200	Hang-sure	304 STAINLESS STEEL	3	10,020	H320, M260, L150
CF12J304	1200	J-Hook	304 STAINLESS STEEL	3	10,020	H320, M260, L150
CF14H304	1400	Hang-sure	304 STAINLESS STEEL	3	11,040	H280, M210, L115
CF14J304	1400	J-Hook	304 STAINLESS STEEL	3	11,040	H280, M210, L115
430 STAIN	ILESS STE	EL SERIES		1		'
CF9HBS	900	Hang-sure	430 STAINLESS STEEL	3	4,920	H360, M260, L160
CF9JBS	900	J-Hook	430 STAINLESS STEEL	3	4,920	H360, M260, L160
CF12HBS	1200	Hang-sure	430 STAINLESS STEEL	3	10,020	H320, M260, L150
CF12JBS	1200	J-Hook	430 STAINLESS STEEL	3	10,020	H320, M260, L150
CF14HBS	1400	Hang-sure	430 STAINLESS STEEL	3	11,040	H280, M210, L115
CF14JBS	1400	J-Hook	430 STAINLESS STEEL	3	11,040	H280, M210, L115
ALUMINI	JM SERIES	I			1	1
CF9HWE	900	Hang-sure	WHITE	3	4,920	H360, M260, L160
CF9JWE	900	J-Hook	WHITE	3	4,920	H360, M260, L160
CF12HWE	1200	Hang-sure	WHITE	3	10,020	H320, M260, L150
CF12JWE	1200	J-Hook	WHITE	3	10,020	H320, M260, L150
CF12H4WE	1200	Hang-sure	WHITE	4	10,800	H290, M220, L125
CF12J4WE	1200	J-Hook	WHITE	4	10,800	H290, M220, L125
CF14HWE	1400	Hang-sure	WHITE	3	11,040	H280, M210, L115
CF14JWE	1400	J-Hook	WHITE	3	11,040	H280, M210, L115
CF14H4WE	1400	Hang-sure	WHITE	4	11,880	H255, M185, L105
CF14J4WE	1400	J-Hook	WHITE	4	11,880	H255, M185, L105
RATTANS	SERIES	I				
CF13HAW	1300	Hang-sure	RATTAN WHITE	4	7,800	H200, M150, L85

Accessories

LIGHT KITS

Cat No	Finish	Diameter
CFOLWE	White	245mm
CFOLBS	Brushed Stainless Steel	245mm
CFCLWE	White	190mm
CFCLBS	Brushed Stainless Steel	190mm

DOWNRODS

Cat No	Mounting	Finish	Length
CFDR750HWE	Hang-sure	White	750mm
CFDR750JWE	J-Hook	White	750mm
CFDR750HBS	Hang-sure	Brushed Stainless Steel	750mm
CFDR750JBS	J-Hook	Brushed Stainless Steel	750mm
CFDR1500HWE	Hang-sure	White	1500mm
CFDR1500JWE	J-Hook	White	1500mm

REPLACEMENT BLADE SETS

Cat No	Description	Finish
CFBL9WE	Single blade for CF9HWE & CF9JWE	White
CFBL9BS	Single blade for CF9HBS & CF9JBS	430 Stainless Steel
CFBL12WE	Single blade for CF12HWE, CF12JWE, CF12H4WE & CF12J4WE	White
CFBL12BS	Single blade for CF12HBS & CF12JBS	430 Stainless Steel
CFBL14WE	Single blade for CF14HWE, CF14JWE, CF14H4WE & CF14J4WE	White
CFBL14BS	Single blade for CF14HBS & CF14JBS	430 Stainless Steel
CFBL12304	Single blade for CF12H304 & CF12J304	304 Stainless Steel
CFBL14304	Single blade for CF14H304 & CF14J304	304 Stainless Steel
CFBL12316L	Single blade for CF12H316L & CF12J316L	Full marine grade 316 Stainless Steel
CFBL14316L	Single blade for CF14H316L & CF14J316L	Full marine grade 316 Stainless Steel

REMOTE CONTROL

Cat No	Description
CFREMOTEH	Remote control kit for Hang-sure Ceiling Fans
CFREMOTEJ	Remote control kit for J-Hook Ceiling Fans

NOTES:



HPM Legrand Australia

Building 4, Nexus Industry Park 43-47 Lyn Parade Prestons NSW 2170 1300 369 777 www.hpm.com.au

HPM Legrand New Zealand

106 - 124 Target Road Glenfield Auckland 0627 0800 476 009 www.hpm.co.nz