## **AUTOMATIC INFRA RED DESIGNER INTERNAL SENSOR**

An intelligent, energy conserving down light that is ideal for low traffic areas.

- Functional 12V halogen gimble down light.
- 360° PIR sensor.
- Supplied with transformer and lamp.
- Ideal for low traffic areas, eg staircase, lobby, pantry, toilet, corridor.





12V Dichroic 50W closed front

## **MATERIALS/FINISH**


Frame	Cast alloy construction in powder coat finish. Low tension spring clips for reduced ceiling damage issues.
INSTALLA	TION/MOUNTING
Mounting	2-point spring fixation Twist-lock external lamp access. Gimble version up to 40° external tilt.
Controls	Dip switch setting flexible. Standalone operation only.

TECHNICAL		
Designed to comply with	AS/NZS 60598	
Class rating	Class 3 electrical	
IP	20	
Operation range	0°C to +40°C	
Lux control	24hr, dusk, night	
PIR sensitive	low, med, high	
Time off delay	5 secs to 5 mins	
Approach detection	360°	
Activation cone	130°	
Sensitivity	6 metres	
Input Voltage	12Vac	
Transformer Input Voltage	220V-240V~50Hz	



DIMENSIONS				
Product	А	В	Tilt angle	Cutout ø
MPES700K	116	113	0-40°	100

A= WIDTH, B= HEIGHT All measurements are in millimetres.



SPECIFICATION GUIDE				
Product	Product Description	Watts		
MPES700K	*Integral PIR sensor down light kit White.	50W		
MPES700KBC	*Integral PIR down light kit Brushed Chrome.	50W		
*Supplied complete with transformer and 50W 38° closed dichroic				

complete with transformer and 50W 38° closed dichroic.

NOTE: All specifications correct at time of printing. Specifications are subject to change without notice.