

Data Sheet

Weatherproof Light Sensitive Switch IP56, 10A



CAT NO. PE170/10



Cat No	PE170/10
Description	Weatherproof Light Sensitive Switch
Operation	Turn Lights on from sunset to sunrise
Contacts	Normally Open
Colour	Grey base with opalescent cover
Supply voltage	230 - 240 Va.c. \pm 6%
Frequency	50 Hz
Connection Type	3 wires
Weatherproof rating	IP56
Maximum Load	2400W Incandescent 2400W Halogen 2400VA Fluorescent 1000W LED
Minimum Load	5W
Stand-by power consumption at V_{in}	\leq 1 W
Operating Temperature	0° to 50°C
Unit Size	83 W x 83 H x 56 D mm

Weatherproof Light Sensitive Switch IP56, 10A

CAT NO. **PE170/10**



- Suitable for all commercial and residential installations
- Weatherproof rating IP56
- Multiple side and back cable entries 25mm Ø
- Low standby power consumption < 1W
- Surface mount
- Easy to install

Single product		
Cat No	Dimensions	Barcode
PE170/10	88 W x 72 H x 115 Dmm	9310539013848

Outer box (QTY 60)		
Cat No	Dimensions	Barcode
PE170/10	397 W x 375 H x 390 Dmm	9321001434580

HPM Legrand - AUS
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.