

# Excel Light Sensor – with or without Neutral



CAT NO. **XLP912WEWE & XLP913WEWE**



- Ideal for simple light control
- Suitable for commercial and residential use
- Helps reduce energy consumption
- Adjustable detection range: 3 – 10m
- Adjustable time delay: 1sec – 16min
- 2 models:
  - With neutral, 3 wire 1000W-compatible with compact fluorescent bulbs and tubes up to 500VA
  - Without neutral, 2 wire 400W up to 400VA



Product specifications		
Cat No	XLP912WEWE	XLP913WEWE
Supply voltage	230-240V a.c.	230-240V a.c.
2 or 3 wire	3 wire	2 wire
Minimum load	0W	40W
Terminal capacity	2 x 1.5mm <sup>2</sup> or 1 x 2.5mm <sup>2</sup>	
IP rating	IP41	
Storage temperature	0°C to +35°C	
Operating temperature	0°C to +35°C	
Resistant to the following agents	Hexane, methylated spirits, soapy water, diluted ammonia, diluted pure bleach (10%), glass cleaning substance, pre-impregnated wipes	
Not resistant to the following agents	Acetone, tar remover, trichloroethylene	

Packaging specifications			
Cat No	Single unit barcode	Inner box barcode	Inner Qty
XLP912WEWE	9321001389729	9321001389736	7
XLP913WEWE	9321001389743	9321001389750	7

## Excel Light Sensor – with or without Neutral

CAT NO. **XLP912WEWE & XLP913WEWE**

HPM Legrand - AUS  
1300 369 777  
www.hpm.com.au

HPM Legrand - NZ  
0800 476 009  
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or  
HPM Legrand Sales Office for pricing.