

Excel No-contact Light Switch



CAT NO. **XLP914WEWE**



- Light switch that does not require physical touching
- Unique and innovative
- Suits environments with strict hygiene requirements such as hospitals or professional kitchen
- Pass hand within 50mm of the sensor to turn switch on
- Up to 5 no-contact switches can be wired in parallel
- Features a blue LED indicator
- Easy to find in the dark



Product specifications	
Voltage	230-240V a.c.
Maximum Load Incandescent 240V halogen 12V halogen with electronic or wirewound transformer Linear fluorescent Compact fluorescent Fan motor	1000W 1000W 500VA 500VA 500VA 100VA
Stand-by power	0.6W
Terminal capacity	2 x 1.5mm ² or 1 x 2.5mm ²
IP rating	IP41
Storage temperature	-10°C to +70°C
Operating temperature	-5°C to +50°C
Resistant to the following agents	Hexane, methylated spirits, soapy water, diluted ammonia, diluted pure bleach (10%), glass cleaning substance, pre-impregnated wipes, diluted hydrogen peroxide (35%)
Not resistant to the following agents	Acetone, tar remover, trichloroethylene

Packaging specifications			
Cat No	Single unit barcode	Inner box barcode	Inner Qty
XLP914WEWE	9321001389767	9321001389774	4

Excel No-contact Light Switch

CAT NO. **XLP914WEWE**

HPM Legrand - AUS
1300 369 777
www.hpm.com.au

HPM Legrand - NZ
0800 476 009
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or
HPM Legrand Sales Office for pricing.