

CAT NO. **XLP926WEWE**, **XLP927WEWE** & **XLP928WEWE**



XLP926WEWE



XLP927WEWE



XLP928WEWE

- Standard white light, blue light or double scenario red/green light to indicate the status of an area e.g. if occupied or free
- LED for low energy consumption
- Ideal for health care and office building projects
- Stickers/signs must be ordered separately
- Choose between 2 levels of brightness – 0.2W or 1W



Product specifications	
Voltage	230-240V a.c.
Light source	LED
Terminal capacity	1 x 2.5mm ² or 2 x 1.5mm ²
IP rating	IP41
Storage temperature	-10°C to +70°C
Operating temperature	-5°C to +50°C
Resistant to the following agents	Hexane, methylated spirits, soapy water, diluted ammonia, diluted pure bleach (10%), glass cleaning substance, pre-impregnated wipes, diluted hydrogen peroxide (35%)
Not resistant to the following agents	Acetone, tar remover, trichloroethylene

Product codes	
Cat No.	Description
XLP926WEWE	Excel signal system white
XLP927WEWE	Excel signal system blue
XLP928WEWE	Excel signal system red/green 2 colours

Packaging specifications		
Cat No	Single unit barcode	Inner box barcode
XLP926WEWE	9321001389941	9321001389958
XLP927WEWE	9321001389965	9321001389972
XLP928WEWE	9321001389989	9321001389996

Excel Signal System

CAT NO. **XLP926WEWE, XLP927WEWE & XLP928WEWE**

HPM Legrand - AUS
1300 369 777
www.hpm.com.au

HPM Legrand - NZ
0800 476 009
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or
HPM Legrand Sales Office for pricing.