

Important:

- This product has electronic components, handle with care. Check contents on opening. When illuminated, the surface of this product will become hot. Ensure the product is in good condition before installation. Do NOT pull or carry the product by the incoming power cable.
- Please follow instructions carefully before conducting installation or maintenance. Installation to be carried out by qualified licensed electrician in accordance with local wiring regulations.

Installation:


- Disconnect mains supply before installing, servicing or maintaining the luminaire.
- The supplementary lanyard that is supplied with the product must be used and installed in all applications.
- The main attachment to the ceiling (not supplied) must be able to withstand 25kg of strain. The highbay is supplied with 1.5m flex and plug and supplied with a 40cm lanyard for supplementary protection against failure of the main attachment.
- In some situations the supplied lanyard may not be long enough and the installer will need to supply their own. The new lanyard must be able to withstand 25kg of strain.
- The supplementary means of protection must be fitted in all applications. Both the main attachment and lanyard must not exert any strain on the power cord once installation is complete.
- The IP65 rating does not apply to mains connection (plug and lead)

Maintenance:

- Poor installation techniques, exposure to excessive heat, sunlight, and power supply extremes will all lead to accelerated aging and premature failure of a luminaire. To ensure your lighting product operates efficiently and reliably the product must be installed in accordance with relevant standards, good practices and these instructions.
- The LED light source and driver are not replaceable.

Specifications:

Model	Voltage/ Frequency	Wattage	Power Factor	Nominal Initial Lumens	Colour Temperature	Weight
684700	240V/50Hz	183W	>0.9	17,800 lm	5700K	6.9 Kg



Disclaimers:

1. The Highbay must be installed and used as per these instructions.
2. This product must be securely attached to a suitable structural member of the installation.
3. This product **MUST** be installed with a secondary means of restraint that is mechanically independent from the primary mechanical fixing.
4. An IP rating of IP65 is generally considered suitable for external walls with supplementary protection such as overhanging eaves.
5. Lamp life is an average and will be reduced by frequent switching.
6. This product has been designed to operate in ambient temperatures: 0°C to 40°C.
7. This product is not suitable for installation in hazardous and/or corrosive areas such as marine environments.
8. Electrical installations periodically receive transient over voltages. This product has been designed to minimise the effect of such voltages on connected equipment. It may not give full protection for extreme over-voltage transients such as those resulting from a close lighting strike.
9. This product has been designed to operate on a nominal supply voltage of 230V - 6% to 240Va.c. + 6%.
10. After installation this product must be tested as required by the appropriate government and/or statutory regulations.
11. This product utilises intellectual property in the form of registered designs, trademarks, and/or patents. Such intellectual property remains the property of HPM Legrand in all cases.
12. HPM Legrand reserves the right to modify the specification of this product at any time.
13. This LED product can only be serviced by HPM Legrand or an approved service agent.
14. The product is not designed to be installed in applications where a high level of vibration is present or may be subject to a high level of impacts (such as in sports halls) or corrosive or salt laden environments.
15. This product should only be cleaned with a damp cloth. Cleaning agents and solvents should not be used.
16. This product should not be cleaned with a hose.
17. The IP rating of this product is only valid when all applicable seals, glands and their appropriate cables are installed correctly.
18. This product has been designed to minimise the effects of interference from off peak electricity signals. Interference in the form of light flicker is still possible in some cases depending on proximity to the signal injection point.
19. This product has been designed with short circuit protection features. Very high short circuit currents may still damage the product.
20. Adequate ventilation around the product must be maintained or the unit may overheat.
21. This product must be cleaned periodically from dust and other contaminants.
22. Please be aware that LED light sources degrade over time. We recommend the LED source or fitting is replaced every 7 years.
23. This LED product can only be serviced by HPM Legrand or an approved service agent.

Warranty

Legrand Australia Pty Ltd guarantees this lighting unit for a period of 5 years from date of despatch, solely against failure arising from faulty materials or workmanship, and provided that the unit has been stored, shipped, installed, used and maintained in accordance with the manufacturers instructions and relevant standards. Misuse, installations exceeding Ta 40°C for no more than 14 hours per day, negligence or modification of the unit voids all warranties. Consult Legrand Australia Pty Ltd Conditions of Sale for details on warranty liability. If this lighting unit is faulty, return the unit freight pre-paid to your point of purchase, or contact Legrand Australia Pty Ltd on 1300 369 777.

Customer Service

For all Customer Service and Technical Support enquires please call Monday to Friday during business hours.

Legrand Australia
1300 369 777
www.legrand.com.au

Legrand New Zealand
0800 476 009
www.legrand.co.nz

ABN: 31 000 102 661