



Superfast Charging

NOW
AVAILABLE AS
A COMPLETE
USB POWERPOINT

Excel Double Powerpoint with Dual USB Charger

2 × 2.1A!



XL777 USB2PSWE

Excel Double Powerpoint with Dual USB Charger →



2 × 2.1A USB sockets for faster charging



Charges 2 × tablets, smart phones or MP3/4 players simultaneously



Perfect for kitchens, bedrooms, offices, schools and more

DOUBLE POWERPOINT WITH DUAL USB CHARGER

Available as complete USB powerpoint or dual USB mechanism to fit in switches and powerpoints



Cat No.	XL777USB2PSWE*	770USB2PSMW
Description	Excel double powerpoint, 10A with dual USB charger mechanism	Excel dual USB charger mechanism
Colour	White	White
Nominal input voltage	230-240V a.c. \pm 6%	230-240V a.c. \pm 6%
Nominal input frequency	50 Hz	50 Hz
Nominal input current	250mA	250mA
Current	10A	N/A
Stand-by power consumption at V_{in}	\leq 0.15W	\leq 0.15W
Nominal output voltage	V_{out} : 5 VDC \pm 5%	V_{out} : 5 VDC \pm 5%
Nominal output current	2 x 2.1A	2 x 2.1A
Energy star level "V"	\leq 78% measured at USB socket output side	\leq 78% measured at USB socket output side
Safety standard	AS/NZS60950-1, AS/NZS 4665	AS/NZS60950-1, AS/NZS 4665
Protection class	Class II	Class II
Overload protection (USB circuit)	4.6A \pm 0.1A	4.6A \pm 0.1A
Surge protection	4,500A, 150 joules	4,500A, 150 joules
Operating temperature	5° to 35°C	5° to 35°C

*Chargers may not be suitable for all installations.

COVERPLATE COLOUR OPTIONS



HPM Legrand Australia
1300 369 777
www.hpm.com.au

HPM Legrand New Zealand
0800 476 009
www.hpm.co.nz

