

Datasheet

Securit LED DALI Emergency


CAT. NO. 684770/D, 684771/D, 684772/D, 684773/D, 684774/D,
684775/D, 684776/D, 684777/D, 684778/D, 684779/D



684770/D



684775/D

Operation Mode	Maintained
Nominal Input Voltage	230 - 240 V a.c. 50 Hz
Battery	Ni-MH 3.6 V, 2.1 Ah
Power Consumption	2.6 W hrc/ 1.8 W lrc
Inrush Current	10 A peak
Light Source Life (LSL)	50,000 hrs
Body Construction	Zinc Coated Steel finished in White Powder Coated
Diffuser Construction	Unbreakable flexible Thermo plastic
Fixing screws	Anti- tamper Resitork
Operating Temperature	10° C to 40° C
IP Rating	IP20
IK Rating	IK06
Product Weight	1.9 Kgs (Surface Model) 2.2 Kgs (Recess Model)
Compliance	IEC 62385, AS/NZS 2293, AS/NZS 60598
Product Marking	  

*hrc- high rate charge, lrc- low rate charge.

Securit LED DALI Emergency

CAT. NO. **684770/D, 684771/D, 684772/D, 684773/D, 684774/D, 684775/D, 684776/D, 684777/D, 684778/D, 684779/D**



FEATURES

- Unbreakable flexible thermo plastic diffuser.
- Diffuser cannot be used as a weapon if dislodged.
- Anti-tamper resitork screws to prevent removal of the unit.
- Thick 6mm polycarbonate panel to prevent entry to electronic components and LEDs.
- Simple to install with quick connect terminal block.
- DALI monitored.
- 1 Year Warranty
- Designed and Manufactured in Australia.

SPACING TABLE

Maximum Spacing between luminaires for 0.2 lux (Australia)						
Mounting Height (m)	2.1	2.4	2.7	3.0	3.3	3.6
C ₀ : E1.25	4.1	4.1	0.0*	0.0*	0.0*	0.0*
C ₉₀ : E1	3.7	0.0*	0.0*	0.0	N/A	N/A

As per AS/NZS 2293:2018

* - exit sign satisfies the requirement to illuminate the doorway or potential hazard, however without a spacing for this mounting height as per AS/NZS 2293:2018 clause 4.5.

N/A - exit sign without a spacing when installed at this mounting height.


Note: For 1.0 lux (New Zealand), this exit sign has no spacing when installed at these mounting heights.

Securit LED DALI Emergency

CAT. NO. 684770/D, 684771/D, 684772/D, 684773/D, 684774/D,
684775/D, 684776/D, 684777/D, 684778/D, 684779/D




DIMENSIONS




Cat. No.	Description
RECESSED	
684770/D	SECURIT LED SS RM
684771/D	SECURIT LED SS RML
684772/D	SECURIT LED SS RMR
684773/D	SECURIT LED DS RM
684774/D	SECURIT LED DS RML/R
SURFACE MOUNTED	
684775/D	SECURIT LED SS RM
684776/D	SECURIT LED SS RML
684777/D	SECURIT LED SS RMR
684778/D	SECURIT LED DS RM
684779/D	SECURIT LED DS RML/R
ACCESSORIES	
659464	L- BRACKET- White
659465	WALL BRACKET- White

RM = Running Man Straight, RML = Running Man Left, RMR = Running Man Right
DS = Double sided, SS = Single sided,


ACCESSORIES




L- BRACKET



WALL BRACKET



WALL BRACKET



L- BRACKET

Note: All the dimensions are in mm.

Legrand Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.

