

Datasheet

Excel / Linea™

USB Charger Mechanism Type C

CAT. NO. 770USB1CMWE



A brand of legrand®



770USB1CMWE

Cat. No.	770USB1CMWE
Colour	White (WE)
Description	Excel Life™ USB Charger Mechanism Single Type C
Nominal Input Voltage	230-240 V a.c. 50 Hz
Nominal Input Current	250 mA
Stand-by Power Consumption	< 0.1 W
Nominal Output Voltage	5V d.c. 3A / 9V d.c. 3A / 12V d.c. 3A / 15V d.c. 3A / 20V d.c. 3A
Nominal Output Power	60 W
Energy Efficiency	Level VI, ≥ 84% measured at USB socket output side
Protection Class	Class II
Overload Protection (on output)	3.4 A ± 0.2 A
Surge Protection	4,500A, 150 joules
Operating Temperature	5°C to 40°C
Dimensions (W x H x D)	21 x 21 x 35 mm
Safety Standard	AS/NZS 60950-1, AS/NZS 4665, AS/NZS 3100

Excel / Linea™ USB Charger Mechanism Type C

CAT. NO. 770USB1CMWE



A brand of **legrand**




Single product		
Cat. No.	Barcode	Dimensions (W x H x D)
770USB1CMWE	9321001469902	101 x 101 x 54 mm

Outer box (QTY 12)		
Cat. No.	Barcode	Dimensions (W x H x D)
770USB1CMWE	9321001470014	200 x 200 x 83 mm

FEATURES

- USB charger Power Delivery: 60 W
- 1 x Type C USB port for latest devices and future releases.
- Capable of charging laptops and gaming consoles, smartphones and tablets at full speed.
- Charging module installed in wall cavity.
- To be installed in Excel/Linea switch plates or powerpoints with an extra mechanism hole.
- Suitable for all commercial and residential installations such as kitchens and bedside tables.
- Overload protection on output (USB circuit)
- Low standby power consumption: < 0.1W
- Indoor use only.



Legrand - Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand - New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.



LE14253AA

03/2023