



Specifications:

For indoor use only
Suitable for connection of copper wire

Cat No.	HL20F HL20FM	HL30F HL30FM	HL40F HL40FMC
Rated operational voltage	415V a.c.		
Short circuit withstand strength	10kA		
Rated insulation voltage	1000V		
Rated current board	100A		
Standard	AS/NZS 3000:2007		
Complies with	AS/NZS 3439.3		
Product size (W x H x D)	300 x 385 x 95mm	335 x 400 x 110mm	455 x 530 x 110mm
Wall cut-out size (W x H x D)	273 x 358 x 65mm	310 x 375 x 65mm	430 x 505 x 65mm

HL**F = flush-mounted distribution board HL**FM = flush-mounted meter board
HL**FMC = flush-mounted meter & distribution board

Wiring:

ATTENTION - Ensure link wires provided are fitted between all Neutral and Earth busbars, where appropriate.
No link between the Neutral and Earth Busbars is required on busbars dedicated to RCD protected circuits.

Contents:

Cat No.	RCD Neutral Bar	Earth Bar	Neutral Bar	Phase Bar Comb	Pole filler strip	Circuit ID Label sheet	Neutral/Earth links
HL20F	4	1	1	2	2	2	1
HL30F	5	1	1	2	2	2	1
HL40F	6	2	1	2	2	2	1
HL20FM	0	0	0	0	0	0	0
HL30FM	0	0	0	0	0	0	0
HL40FMC	4	1	1	1	2	1	1

Cat No.	Barcode	Qty
HL20F	9321001431053	1
HL20F	9321001431084	8
HL30F	9321001431060	1
HL30F	9321001431091	5
HL40F	9321001431077	1
HL40F	9321001431107	3

Cat No.	Barcode	Qty
HL20FM	9321001457053	1
HL20FM	9321001457084	8
HL30FM	9321001457060	1
HL30FM	9321001457091	5
HL40FMC	9321001457077	1
HL40FMC	9321001457107	3

Warranty

HPM Legrand will honour all statutory guarantees that you as a consumer are entitled to rely upon under the Australian and New Zealand Consumer Laws against a manufacturer, including a guarantee that this product is of acceptable quality.

To make a claim under any statutory guarantee you should first contact the supplier, or retailer from whom you purchased this product.

Customer Service

For all Customer Service and Technical Support enquires please call Monday to Friday during business hours.

HPM Legrand Australia
1300 369 777
www.hpmlgrand.com.au

HPM Legrand New Zealand
0800 476 009
www.hpmlgrand.co.nz

ABN: 31 000 102 661