Datasheet Bulkhead 360 LED CAT. NO. 659070LI, 659071LI





659070LI

659071LI

Cat. No.	659070LI	659071LI		
Description	BULKHEAD R 360 LED	BULKHEAD R 360 LED		
Design	Plain	Guard		
Nominal Input Voltage	230 - 240 V a.c. 50 Hz			
Operating Mode	Switch Maintained			
Battery	Li-ion 12.8 V, 1.5 Ah			
Power Pack Wattage	4 W			
Circuit Power	22 W			
Inrush Current	28 A peak			
Light Source Life (LSL)	50,000 hrs			
Mains Luminaire Output (lm)	1800	1600		
Classification	C ₀ / C ₉₀ : D80			
Colour Temperature (K)	4000 K			
CRI	>80			
Luminaire Efficacy (lm/W)	81	72		
Power Factor	>0.9			
Weight (kg)	4.8	4.9		
Ballast type	Fixed output/Non-Dimmable			
Operating Temperature	10°C to 40°C			
IP Rating	IP65			
Impact Rating	IK10			
Body Construction	Die-cast Aluminium			
Diffuser Construction	Frosted Polycarbonate			
Compliance	AS/NZS 60598, AS/NZS 2293, AS/NZS 4268, AS CISPR 15			
Product Marking	🗟 🕒 R-NZ			







Bulkhead 360 LED


CAT. NO. 659070LI, 659071LI



FEATURES

- L70 @ 50,000 hours
- Large terminal block.
- Embedded Bluetooth for smart device connectivity.
- Low Power Wide Area Network type of communications utilising the LoRa platform.
- LoRa communication to maximise reliability, coverage and infiltration.
- iSmart[™] temperature sensing technology for Li-ion battery.
- Electronics designed to lengthen the life of the battery.
- Robust die cast aluminium construction.
- Available in plain or guard.
- 5 Year Warranty
- Manufactured in Australia.

DIMENSIONS



SPACING TABLE

Maximum Spacing between luminaires for 0.2 lux (Australia)						
Mounting Height (m)	2.4	2.7	3.0	3.3		
D80	13.2	14.8	16.5	18.1		

As per AS/NZS 2293:2018

Maximum Spacing between luminaires for 1.0 lux (New Zealand)					
Mounting Height (m)	2.4	2.7	3.0	3.3	
D80	12.5	12.9	13.3	13.6	

As per AS/NZS 2293:2018

Note: Spacing table based on ceiling mounting.

Legrand - Australia 1300 369 777 www.legrand.com.au ABN 31 000 102 661

Legrand - New Zealand 0800 476 009 www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subjected to change without prior notice.

