

# Datasheet

## Excel Life™ Medical Range UPS Status indicator, Antimicrobial

CAT. NO. **ECUPSALCABU**



<b>Cat. No.</b>	<b>ECUPSALCABU</b>
<b>Description</b>	Excel Life UPS Status Indicator (UPSSI), Antimicrobial
<b>Power Supply</b>	100 - 240 V a.c. 50Hz, 55/36 mA Max, 47-63Hz (From UPS)
<b>Fuse Rating</b>	The fuse is user non-replaceable
<b>Mains Indicator</b>	Green LED indicates mains ON
<b>Alarm Indicators</b>	Flashing Red LED indicates UPS in Emergency Mode
<b>Audible Alarm</b>	Pulsing buzzer indicates UPS in Emergency Mode
<b>Mute Function</b>	1-4 hrs in 1 hr increments
<b>Alarm Output Option</b>	Voltage free contact (normally open – closes on alarm)
<b>Alarm Output Contact Rating</b>	1 A 24 V d.c. / 0.5 A 125 V a.c.
<b>Terminal size</b>	1 x 2.5 mm <sup>2</sup> or 2 x 1.5 mm <sup>2</sup> (Screw terminals)
<b>Operating Temperature</b>	0° C to 55° C
<b>Mounting</b>	Wall mount (84 mm) Mounting centres

# Excel Life™ Medical Range

## UPS Status indicator, Antimicrobial



CAT. NO. **ECUPSALCABU**



Single product	
<b>Cat. No.</b>	<b>Barcode</b>
ECUPSALCABU	9321001503613

- Visual alarm: "Mains ON" and "UPS Emergency mode" LED indicators on the front plate.
- Audible alarm with mute option (configurable to "time out" from 1 to 4 hours).
- Optional relay alarm output voltage free contact.
- In case of Mains failure, alarms contacts will remain in "Closed alarm" state.
- Chemical Resistant and Antimicrobial\*

*Antimicrobial Specifications			
<b>Maintenance</b>	Surface cleaning with cloth: Hospital-grade water-based cleaners only. Do not use any solvent based cleaner such as acetone, tar-remover or trichloroethylene.		
<b>Antimicrobial Properties</b>	Challenge Organism	Polycarbonate alloy in fascia parts	Polycarbonate alloy in switch dolly
		Reduction Coefficient/Kill Rate	
<b>Note:</b> 5 Log = 99.9999% 4 Log = 99.99% 3 Log = 99.9% 2 Log = 99%	<b>Escherichia Coli</b>	2.55 Log / 99.72%	6.72 Log / 99.9999%
	<b>Staphylococcus aureus</b>	2.70 Log / 99.79%	5.22 Log / 99.999%
<p>Tests performed according to JIS Z 2801:2010 (Antimicrobial products – Test for antimicrobial activity and efficacy). Test method is equivalent to procedure detailed in ISO 22196:2011 (Measurement of antibacterial activity on plastics and other non-porous surfaces). Test results available upon request.</p> <p>Not to be used as an alternative or substitute for standard hygienic practices, procedures, or protocols. This device has a long-term antimicrobial effect. Lifespan is dependent upon cleaning procedures and the use of recommended cleaning products.</p> <p>Product manufactured with antimicrobial material based on Ag+ ions. This technology limits the proliferation of bacteria on our devices without increasing antibiotic resistance.</p>			

Legrand - Australia  
1300 369 777  
www.legrand.com.au  
ABN 31 000 102 661

Legrand - New Zealand  
0800 476 009  
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.

