### **Datasheet**

# WP3 LED Weatherproof Batten IP65

- Galaxy with dimmable sensor

CAT. NO. **659302GA, 659305GA, 659308GA** 





Cat. No.		659302GA	659305GA	659308GA
Description		WP3 L6 LED BATTEN MW DIM GALAXY	WP3 L12 LED BATTEN MW DIM GALAXY	WP3 L15 LED BATTEN MW DIM GALAXY
Supply Voltage		230-240 V a.c. 50 Hz		
Operation Mode		Switched Maintained		
Movement sensor type		Microwave		
Classification C <sub>0</sub> /C <sub>90</sub>		C <sub>0</sub> /D80, C <sub>90</sub> /D50	C <sub>0</sub> /D125, C <sub>90</sub> /D80	C <sub>0</sub> /D160, C <sub>90</sub> /D100
Battery		Li-ion 12.8V 1.5Ah		
Light Source		Selectable LED (3000K/4000K/6500K)		
Luminous flux (lm) (Mains mode)	Warm	1900	4220	5410
	Cool	1940	4370	5590
	Natural	1960	4390	5610
Power consumption (W)	Mains only	15	34	43
	Emergency pack	3	3	3
	Total	18	37	46
Luminaire efficacy at 4000K (lm/W)		108	118	122
Power factor		>0.8	>0.9	
Inrush Current		13.6A	35A	
IP Rating		IP65		
IK Rating		IK08		
Retaining clips		304 Stainless Steel		
Body construction		Polycarbonate		
Diffuser		Opal polycarbonate		
Length (mm)		664	1274	1574
Weight (kg)		1.8	2.7	3.3
Compliance		AS/NZS 2293, AS/NZS 60598, AS CISPR 15		
Product marking		<b>ℰ</b> R-NZ		










### WP3 LED Weatherproof Batten IP65

## - Galaxy with dimmable sensor







#### **FEATURES**


- Embedded Bluetooth for smart device connectivity.
- Low Power Wide Area Network type of communications utilising the LoRa platform.
- LoRa communication to maximise reliability, coverage and infiltration.
- iSmart<sup>TM</sup> temperature sensing technology for the LIION battery.
- Electronics designed to lengthen the life of the battery, minimising maintenance costs.
- A premium range of LED weatherproof battens.
- Available in 2 foot, 4 foot or 5 foot lengths.
- Tri-colour LED selection.
- LED Light source life: 150,000hrs, L80 B50 at ambient temperature of 25°C.
  - 250,000hrs, L70 B50 at ambient temperature of 25°C.
- CRI > 90
- Environmentally friendly battery.
- 5 Year warranty.
- Designed and Manufactured in Australia.

#### **DIMENSIONS**





#### **DIMMABLE SENSOR OPERATION**



Legrand - Australia 1300 369 777 www.legrand.com.au ABN 31 000 102 661

Legrand - New Zealand 0800 476 009 www.legrand.co.nz Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.

