Datasheet RJ45 Patch Lead

Cat.No: **PLC6A Series**









Cat. No: PLC6AWE-7.5



Range	PLC6A Series			
Description	Caté A SFTP 26 AWG Patch Leads			
Cable Shield	S/FTP			
Туре	4 pair cables (Non-plenum cable)			
AWG Gauge	26 AWG (Stranded)			
Cable Filler	N/A			
Cable Sleeve	5.9mm 0D			
Insulation Resistance	500ΜΩ			
Connector Type	RJ45 8P8C			
Communication Network Category	Cat 6A			
Assembly Style	Plug to Plug with moulded strain release boot			
Plug Housing Material	Polycarbonate			
Contact Material	Phosphor bronze with 30 micron-inches gold plating			
Contact Resistance	20mΩ			
Wiring Scheme	T568A			
Ambient Air Temperature for Operation	-10°C to 60°C			
Channel Tested	Yes			
Compliance	ISO/IEC 11801, ANSI/EIA-568.2-D, REACH			


RJ45 Patch Lead


Cat.No: PLC6A Series



FEATURES AND BENEFITS

- Patch cords for high speed transmission network Cat 6A.
- Straight RJ45-RJ45 plugs.
- The cord is snagless, it has a strain relief boot to protect the connector lock from being snapped off easily.
- Eco-friendly packaging (Bagless).





SELECTION CHART

LENGTH	BEIGE	BLACK	BLUE	ORANGE	WHITE	RED	YELLOW
0.5 metre	PLC6ABE-0.5	PLC6ABL-0.5	PLC6ABU-0.5				
1 metre	PLC6ABE-1	PLC6ABL-1	PLC6ABU-1		PLC6AWE-1		
1.5 metres	PLC6ABE-1.5	PLC6ABL-1.5	PLC6ABU-1.5		PLC6AWE-1.5		
2 metres	PLC6ABE-2	PLC6ABL-2	PLC6ABU-2		PLC6AWE-2		
3 metres	PLC6ABE-3	PLC6ABL-3	PLC6ABU-3		PLC6AWE-3		
5 metres	PLC6ABE-5	PLC6ABL-5	PLC6ABU-5	PLC6AOR-5	PLC6AWE-5	PLC6ARD-5	PLC6AYE-5
7.5 metres	PLC6ABE-7.5	PLC6ABL-7.5	PLC6ABU-7.5		PLC6AWE-7.5		
10 metres	PLC6ABE-10	PLC6ABL-10	PLC6ABU-10		PLC6AWE-10		
20 metres	PLC6ABE-20	PLC6ABL-20	PLC6ABU-20		PLC6AWE-20		