


Datasheet

Arteor™

Dual USB Charger Mechanism Type A & C

CAT. NO. ARUSBN2ACMWE, ARUSBN2ACMMGN




ARUSBN2ACMMGN

Cat. No.	ARUSBN2ACMWE	ARUSBN2ACMMGN
Colour	White (WE)	Magnesium (MGN)
Description	Arteor™ Dual USB Charger Mechanism Type A & C	
Nominal Input Voltage	230-240 V a.c. 50 Hz	
Stand-by Power Consumption	75 mW	
Nominal Output Voltage	5 V d.c.	
Nominal Output Current	3 A	
Energy Efficiency	Level VI	
Protection Class	Class II	
Overload Protection (on output)	3.1 A	
Surge Protection	1750 A, 70 joules	
Operating Temperature	5°C to 25°C	
Dimensions (W x H x D)	24 x 26 x 50 mm	
Safety Standard	AS/NZS 61558.2.16, AS/NZS 4665	

Arteor™ Dual USB Charger Mechanism Type A & C

CAT. NO. ARUSBN2ACMWE, ARUSBN2ACMMGN



Single product		
Cat. No.	Barcode	Dimensions (W x H x D)
ARUSBN2ACMWE	9321001516644	101 x 101 x 54 mm
ARUSBN2ACMMGN	9321001516583	

Outer box (QTY 12)		
Cat. No.	Barcode	Dimensions (W x H x D)
ARUSBN2ACMWE	9321001516804	200 x 200 x 83 mm
ARUSBN2ACMMGN	9321001516743	

FEATURES

- 15 W Charging capacity over 2 ports.
- 1 x Type C USB port for latest devices and future releases.
- Capable of charging 2 smartphones simultaneously or 1 tablet at full speed.
- Suitable for smartphones, tablets, fitness bands and running watches.
- To be installed in Arteor™ switch plates 1 to 3 Gang (not suitable for 4 to 6 gang installation) or powerpoints with an extra mechanism hole.
- Suitable for all commercial and residential installations such as kitchens and bedside tables.
- Overload protection on output (USB circuit).
- Low standby power consumption: 75 mW.
- Indoor use only.

Legrand - Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand - New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.



LE1424AA

04/2023