

# Datasheet

Excel/Linea™

## Dual USB Charger Mechanism Type C

CAT. NO. USBN2CMWE, USBN2CMBL



A brand of legrand®



USBN2CMWE


Cat. No.	USBN2CMWE	USBN2CMBL
Colour	White (WE)	Black (BL)
Description	Excel / Linea™ Dual USB Charger Mechanism Type C	
Nominal Input Voltage	230 - 240 V a.c. 50 Hz	
Stand-by Power Consumption	75 mW	
Nominal Output Voltage	5 V d.c.	
Nominal Output Current	3 A	
Energy Efficiency	Level VI	
Protection Class	Class II	
Overload Protection (on output)	3.1 A	
Surge Protection	1750 A, 70 joules	
Operating Temperature	5°C to 25°C	
Dimensions (W x H x D)	24 x 26 x 50 mm	
Safety Standard	AS/NZS 61558.2.16, AS/NZS 4665	

# Excel/Linea™ Dual USB Charger Mechanism Type C

CAT. NO. **USBN2CMWE, USBN2CMBL**



A brand of **legrand**



Single product		
Cat. No.	Barcode	Dimensions (W x H x D)
USBN2CMWE	9321001516552	101 x 101 x 54 mm
USBN2CMBL	9321001526254	

Outer box (QTY 12)		
Cat. No.	Barcode	Dimensions (W x H x D)
USBN2CMWE	9321001516712	200 x 200 x 83 mm

## FEATURES

- 15 W Charging capacity over 2 ports.
- 2 x Type C USB port for latest devices and future releases.
- Capable of charging 2 smartphones simultaneously or 1 tablet at full speed.
- Suitable for smartphones, tablets, fitness bands and running watches.
- To be installed in Excel and Linea™ switch plates 1 to 3 Gang (not suitable for 4 to 6 gang installation). Refer to Instruction sheet for installation in a Double Powerpoint with extra hole.
- Suitable for all commercial and residential installations such as kitchens and bedside tables.
- Overload protection on output (USB circuit).
- Low standby power consumption: 75 mW.
- Indoor use only.

Legrand - Australia  
1300 369 777  
www.legrand.com.au  
ABN 31 000 102 661

Legrand - New Zealand  
0800 476 009  
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or  
Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.

LE14245AB