

Your usual Sales office www.legrand.com

### **Product Environmental Profile**

Hypra panel mounting sockets from 16A to 32A IP 44 and IP 67





#### ■ LEGRAND'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites Of all Legrand sites worldwide, over 80% are ISO 14001-certified (sites belonging to the Group for more than five years)..
- Involve the environment in product design Provide our customers with all relevant information (composition, consumption, end of life, etc.). Reduce the environmental impact of products over their whole life cycle..
- Offer our customers environmentally friendly solutions
  Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.



#### REFERENCE PRODUCT

Fonction	Allow power distribution to all type of electrical devices from a voltage 200/250V at a current of 16A, polarity 2P+E on IP 44, on a lifetime of 20 years, complies with standards IEC 60309-1 and IEC 60309-2, on a lifetime of 20 years, based on 30% load and 30% used time.						
Reference Product	Sign Street Principles  Sign S						
	Catalogue Numbers 052018						
	Panel mounting sockets fixing centre Hypra - IP 44 -200/250V~ -16A -2P+E -Plastic						

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company



#### ■ PRODUCTS CONCERNED

The environmental data for the reference product refers to the following Catalogue Numbers:

#### Références

052018, 052019, 052020, 052022, 052223, 052224, 052218, 052219, 052220, 052718, 052719, 052720, 052918, 052919, 052920, 051126, 051130, 051131, 0511



## Your usual Sales office www.legrand.com

### **Product Environmental Profile**

# Hypra panel mounting sockets from 16A to 32A IP 44 and IP 67





#### ■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It does not contain substances covered by the RoHS Directive (2002/95/EC and its revision 2011/65/EC). It contains none of the 138 candidate list of the REACH regulation dated 19/12/2012

Total weight of Reference Product	134 g (with un	it packaging)				
Plastics as % of weight		Metals as % of weight		Other as % of weight		
PA	73.5%	Copper alloys	20.7%			
SBS	6.8%	Steel	3.4%			
				Packaging as % of weight		
				paper	8.8%	
Total plastics	67.1%	Total metals	24.1%	Total other and packaging	8.8%	

Estimated recycled material content: 10% by mass.



#### MANUFACTURE \_\_\_\_

This Reference Product comes from a site that have received ISO14001 certification..



#### DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency.

The Reference Product is therefore transported over an average distance of 257.4 km by road, 272.8 by plane, 3594 by ship from our warehouse to the local point of distribution into the market in Europe.

Packaging is compliant with european directive 2004/12/EC concerning packaging and packaging waste.

At the packaging end of life, its recycliabilty rate is of 100% (in % of the mass of the packaging)



#### ■ INSTALLATION ■

Installation components not delivered with the product are not taken into account.



#### USE

Servicing and maintenance:

Under normal conditions of use, this type of Product requires no servicing or maintenance

Consumable

No consumables are necessary to use the Reference Product



## Your usual Sales office www.legrand.com

### **Product Environmental Profile**

# Hypra panel mounting sockets from 16A to 32A IP 44 and IP 67





#### ■ END OF LIFE I

Development teams integrate product end-of-life factors in the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.

• Recyclability rate

Calculated using the method described in the IEC/TR 62635 technical report, the recyclability rate of the product is estimated as 90%. This value is based on data collected from a technological channel using industrial procedures. It does not pre-validate the effective use of this channel for end-of-life electrical and electronic products.

#### Separated into:

- Plastic materials (excluding packaging)
- Metal materials (excluding packaging)
- Other materials (excluding packaging)
- Packaging (all types of materials)
: 57 %
: 24 %
: 0 %
: 9 %



#### ■ ENVIRONMENTAL IMPACTS ■

The evaluation of environmental impacts examines the stages of the reference product life cycle: manufacturing, distribution, installation, use, and end of life. It is representative from products marketed and used in Europe, in compliance with the local current standards

The following modelling elements were taken into account:

Manufacture	Unit packaging taken in account. As required by the "PEP ecopassport" programme all transports for the manufacturing of the Reference Product, including materials and components, has been taken in account.
Distribution	Transport between the last Group distribution centre and an average delivery to the sales area
Installation	Installation components not delivered with the product are not taken into account.
Use	<ul> <li>Under normal conditions of use, this type of Product requires no servicing or maintenance</li> <li>No consumables are necessary to use the Reference Product</li> <li>Product category: passive product</li> <li>Use scenario: non-continuous operation for 20 years at 30% of rated load, during 30% of the time. This modelling duration does not constitute a minimum durabilty requirement</li> <li>Energy model: Europe, year 2005</li> </ul>
End of life	In view of the data avalaible on the date of creation of the document, and in accordance with the requirements of the PCR of the «PEP ecopassport» programme, transport of the Reference Product by road only once, over a distance of 1000 km, to a processing site at end of life was counted.
Software used	EIME V5 and its database «Legrand_2012_10_31_version_3, issue de la base CODDE-2012-07»



## Your usual Sales office www.legrand.com

### **Product Environmental Profile**

# Hypra panel mounting sockets from 16A to 32A IP 44 and IP 67





#### ■ ENVIRONMENTAL IMPACTS (continued) ■

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life		
	Contribution to greenhouse effect	1.95E+03	g~CO2	1.12E+03	57%	4.64E+01	2%	0.00E+00	0%	7.77E+02	40%	6.71E+00	< 1%
	Damage to the ozone layer	1.49E-04	g~CFC-11	7.66E-05	51%	3.05E-05	20%	0.00E+00	0%	4.22E-05	28%	1.27E-08	< 1%
Mandatory indicators	Eutrophisation of water	2.00E-01	g~PO43-	1.97E-01	99%	8.63E-04	< 1%	0.00E+00	0%	1.83E-03	< 1%	1.25E-05	< 1%
	Photochemical ozone formation	7.49E-01	g~C2H4	4.37E-01	58%	3.90E-02	5%	0.00E+00	0%	2.72E-01	36%	1.50E-03	< 1%
Manda	Acidification of the air	3.18E-01	g~H+	2.05E-01	64%	8.19E-03	3%	0.00E+00	0%	1.04E-01	33%	1.25E-03	< 1%
	Total energy consumed	3.30E+01	МЈ	1.69E+01	51%	5.45E-01	2%	0.00E+00	0%	1.54E+01	47%	9.46E-02	< 1%
	Consumption of water	9.48E+00	dm3	7.20E+00	76%	5.18E-02	< 1%	0.00E+00	0%	2.23E+00	23%	6.97E-04	< 1%

rs	Depletion of natural resources	2.36E-15	années -1	2.35E-15	99%	7.43E-19	< 1%	0.00E+00	0%	1.75E-17	< 1%	1.37E-19	< 1%
indicato	Toxicity of the air	5.84E+05	m³	4.42E+05	76%	1.13E+04	2%	0.00E+00	0%	1.29E+05	22%	1.85E+03	< 1%
Optional i	Toxicity of the water	5.36E-01	dm³	3.04E-01	57%	6.12E-03	1%	0.00E+00	0%	2.23E-01	42%	2.87E-03	< 1%
Ŏ	Production of hazardous waste	3.11E-02	kg	1.82E-02	59%	7.91E-06	< 1%	0.00E+00	0%	1.29E-02	41%	8.31E-09	< 1%

The environmental impacts of the Reference Product are representative of the products covered by the PEP, which therefore constitute a homgeneous environmental family.

To determine the environmental impact of a product covered by the PEP other than the cat.number (052018), the following rules apply:

- -Distribution, Installation and End of life phases, take the same values
- -Manufacturing phase, multiply the indicators (except Raw material depletion) by the coefficient 3 for the 32A
- -For Raw material depletion indicator, multiply by the coefficient 16 for the 32A
- -Use phases, multiply the indicators by the coefficient 3 for the 32A

The values of these impacts are valid for the context specified in this document. They must not be used directly to draw up the environmental balance sheet for the installation.

Registration number: LGRP-2015-018-V1-en	Drafting rule: PEP-PCR-ed 2.1-FR-2012 12 11 PSR-0005-ed1-FR-2012 12 11				
Authorisation number of checker: VH02	Programme information: www.pep-ecopassport.org				
Date of issue: 04-2015	Validity period: 4 years				
Independent verification of the declaration and data, in accordance with Internal ☐ External ☐	PEP				
In accordance with ISO 14025 :2006 Type III environmental declaration	eco				
The critical review of the PCR was conducted by a panel of experts chaired by J.Chevalier (CSTB)					
The elements of the present PEP cannot be compared with elements from another programme					