

Datasheet

Power Converter (10 to 15A)

CAT NO. REPC11015



A brand of **legrand**



Cat. No.	REPC410
Supply Voltage	230-240V a.c. 50Hz
Max. Load	2400W (10A)
Plug	10A, fully moulded
Outlet	15A
Rated Residual Current	30mA
Typical Trip Time	30ms
Lead	1.0mm flexible heavy duty - 1.8m (10A)
RCBO	Type A
Rated	Indoor use only

Power Converter (10 to 15A)

CAT NO. REPC11015



A brand of **legrand**



Single product		
Barcode	Dimensions (L x W x H)	Weight
9321001435013	134 x 189 x 150mm	1125g

Outer box (Qty 9)		
Barcode	Dimensions (L x W x H)	Weight
9321001435020	420 x 220 x 470mm	10.1kg

- Ideal for providing temporary mains supply to 15A appliances and power tools requiring power for short durations.
- Adapts 10A connection to 15A connection
- 1 x 15A Double pole shuttered outlet for extra safety
- Parking clip to prevent lead unravelling
- Not suitable for use on dedicated, permanently connected caravan sites or construction sites.
- RCBO (10A) protection - combines Residual Current Device (RCD), for fast power cut off reducing the risk of electrocution and Miniature Circuit Breaker (MCB) for overload protection.

Legrand - Australia
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

Legrand - New Zealand
0800 476 009
www.hpm.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.



LE154/70AA

12/2024