

10A & 15A Electresafe Power centre



CAT NO. REPC410 and REPC415



- Ideal for construction sites and workshops
- Built-in RCD safety switch - electromechanical RCD will trip within 30 thousandths of a second if the supply neutral is lost
- A type RCD - protects the supply against AC earth fault currents and pulsating DC fault currents
- Built-in MCB for overload protection
- Double pole shuttered outlets for extra safety
- Parking clip for convenience
- Orange high visibility lead for extra safety
- Rated IP33
- Compatible with portable appliance testers
- 2 year warranty



Product specifications	
Supply voltage	230-240V a.c. 50Hz
Max load	2400V (10A) 3600V (15A)
Rated residual current	30mA
Typical trip time	30ms
Lead	1.0mm flexible heavy duty - 1.8m (10A) 1.5mm flexible heavy duty - 1.8m (15A)
Rated	IP33

Packaging specifications 10A	
Single box quantity	1
Single box dimensions	150mm (L) x 134mm(W) x 189mm(H)
Single box weight	1260g
Single box barcode	9321001370222
Outer (shipper) carton quantity	9
Outer (shipper) dimensions	470mm(L) x 420mm(W) x 220mm(H)
Outer (shipper) carton weight	12.9Kg (G.W.)
Outer (shipper) barcode	9321001370239

Packaging specifications 15A	
Single box quantity	1
Single box dimensions	150mm (L) x 134mm(W) x 189mm(H)
Single box weight	1300g
Single box barcode	9321001370246
Outer (shipper) carton quantity	9
Outer (shipper) dimensions	470mm(L) x 420mm(W) x 220mm(H)
Outer (shipper) carton weight	12.9Kg (G.W.)
Outer (shipper) barcode	9321001370253

10A & 15A Electresafe powercentre

HPM Legrand - AUS
1300 369 777
www.hpm.com.au

HPM Legrand - NZ
0800 476 009
www.hpm.co.nz

CAT NO. **REPC410 and REPC415**

Refer to your group buying office, HPM Legrand Sales Representative or
HPM Legrand Sales Office for pricing.